

AQUASMART 5 RTRP

Troubleshooting



TROUBLE SHOOTING

NO POWER TO THE DISPLAY:

Power point is faulty. Test power point with a known working appliance. If the power point is operational, check the controller in another power point and if there is still no display then send the controller for repair.

RTC-FAIL – This can occur if the unit has been turned off for a prolonged period of time, leave the unit on for ~30 seconds, then turn it off for ~30 seconds before turning it back on.

PIPE/ROOF SENSOR FAULTS:

The following are error messages caused by pool or roof sensor faults;

SENSOR DISCONNECTED OR OPEN CIRCUIT

Sensor cable unplugged from controller, cable damaged, bad cable join or sensor is damaged.

SENSOR SHORT CIRCUIT OR REVERSED

Sensor cable or cable join polarity is incorrect, or sensor is damaged. The positive side of the cable (grey coloured wire) should be wired to the righthand side of the plug, with the screws facing towards you and the cable cable entry at the bottom of the plug. If the cable has been joined ensure no polarity reversal occurs.

Dontek Electronics Pty Ltd

PO Box 239, Bayswater VIC 3153 Australia
Phone: +613 9762 8800 Email: sales@dontek.com.au

ISOLATING SENSOR FAULTS:

Swap the sensor locations. Put the pipe sensor in the roof socket and the roof sensor in the pipe socket.

If the fault moves from pipe to roof or vice versa then it is likely that there is a sensor fault.

If the fault remains the same then the controller may need to be repaired.

PUMP FAULTS:

Ensure the controller has working sensors; otherwise the pump will not operate.

SOLAR PUMP WILL NOT START:

The pump will only ever run for the purpose of automatic heating if the pool is below the temperature limit and solar conditions can provide heating.

The pump may also run for a flush in winter-mode or for manual mode operation. If the pump does not operate then plug the pump into a power point and test operation, if the pump is OK then the controller requires repair.

Check and make sure that the master controller is receiving a transmission from the remote transmitter. Check for a roof sensor fault. If needs be, remount the transmitter to ensure the master controller receives transmissions or install an antennae extension kit [available for purchase separately] to the master controller.

If the controller is showing a “No Flow” error message, check to ensure chlorinator and filtration pump are plugged into the Filter socket and that the filtration pump is running. If a “No flow” error message is displayed and the filtration pump is running, reset the Pump Load Settings as described in INSTALLER SETUP.

PUMP WILL NOT STOP:

Turn off power to the controller and ensure the pump stops. If the pump continues to operate then unplug it from the power point and connect it to the 240Vac socket marked SOLAR at the bottom of the controller.

If the pump is plugged into the controller and won't stop, check to see what is displayed on the controller screen. The controller may be running for heating purposes.

If the pump is still running, and the controller states that nothing should be running, your controller requires repair.

TROUBLE SHOOTING CONTINUED

FILTRATION PUMP WILL NOT START:

Ensure that the filtration pump is plugged into the Chlorinator properly and the Chlorinator is plugged into the Aquasmart5 RTRP FILTER power socket properly. Check the filtration times set in the Aquasmart5 RTRP controller, adjust if required.

Check the power to the FILTER socket by pressing the Mode button until Filter Manual appears. The controller should turn the Chlorinator and Filter pump on for a 3min backwash.

If it still won't start plug the filtration pump straight into a power point and turn on. IF the pump doesn't start then you have an issue with your pump. If the pump is ok, your controller requires repair.

POOL NOT HEATING:

If the controller has stopped pumping and is displaying a higher temperature than expected it may be caused by a pump which is failing to prime. Check the pump and if necessary, prime the pump as per the pump manufacturers' instructions then reset the controller by turning it off/on.

Check the controller LCD screen to see if any sensor faults are present and fix as required.

If the controller is in Standby Mode, it will not heat the pool no matter what the roof temperature is. If it is consistently warm enough, switch the controller back into Heating Mode to start heating your pool.

FACTORY RESET:

Hold down ENTER when power is off, hold down after powering up, releasing after 5 seconds.